

Fully portable 22kW Electric boiler, fully programmable, flexible & perfect for drying, hot water & central heating.

- Underfloor heating testing
- Heating & Hot Water Recovery
- New build construction & refurb
- Flexible: compatible with pumps, hose, plate packs & Air Handling Units
- Underfloor heating screed drying
- Public Sector, Construction, Facilities Management
- Adjustable: full digital controls



Detail	General	Heating	Domestic Hot Water
Output	5 - 22 kW		
Temperature Range		20/72°C	25/65°C
Fuel Type	Electric		
Power Supply	415v 3ph 50Hz		
Running Current	31 Amps		
Plug Type	32A 5 Pin BS4343		
Max Working Pressure		3 Bar	5 Bar
Safety Valves		3 Bar	5 Bar
BMS Outputs	No		
Time Clock	No		
Frost Protection	No		
Flow	55 ltrs/min		
Pump Capacity	4,500 ltr/hr @ 0.6 bar		
Variable Temperature Control	Yes		
Expansion Vessel	10 ltrs		
DHW Circulation System	Yes (separate)		
Flexible Hose Connections	Storz		
Water Connections	Flow / Return / Cold Feed 1"		
Noise Level	45 dBa @ 1mtr		
Weight	50 kg		
Dimensions (WxDxH)	600 x 550 x 1100mm		
Optional Ancillary Equipment	Boost pump - for longer pipe runs		
	Plate pack - for domestic hot water		
	High temperature flexible hose		
	Manifold sets for multiple boiler connection		
	Air handling units for space heating		