

Small footprint trailerised 300kW Boiler, features a compact design & low weight perfect for sites where space is limited.

- Gas or Oil fired burner options available for full flexibility & economy
- Heating & hot water recovery
- Flexible: compatible with pumps, hose, plate packs & Air Handling Units
- Bespoke built at the Cross Rental Services UK facility
- Used in: Public Sector, Construction, Facilities Management
- Oil options can be paired with a small footprint external fuel tank
- Gas options can be connected directly to site supply
- Housed inside a road towable trailer
- Internal tool box, spares & instructions for maintenance
- Can be paired to thermostatically controlled fan coils for flexible delivery of warm air - for events, commercial warehousing & distribution



Detail	General	Heating
Output		300kW
Temperature Range		30-90°C
Fuel Type	Diesel Oil/Natural Gas	
Fuel Connections	External Oil Tank or 2" Gas Train	
Fuel Consumption	30 litres/hour (Oil)	
Power Supply	230v 1ph N+E 50Hz	
Running Current	10 amps	
Plug Type	32A 3pin BS4343	
Max Working Pressure		4 Bar
Safety Valves		4 Bar
Heat Exchanger		No
BMS Outputs	No	
Time Clock	Yes	
Frost Protection	No	
Flow		Max 60,000 litres/hour @ 45°C, 1 bar
Pump Capacity		
Variable Temperature Control	Yes	
Height of Flue Above Ground	2800mm	
Expansion Vessel		300 litres
DHW Circulation System		
Flexible Hose Connections	Storz Twist Lock	
Water Connections	Flow/Return	3" Storz
Re-circulation Connection		
Noise Level	45 dBA @ 10 mtrs	
Handling Options	Trailer Mounted 50mm Tow Ball	
Weight	1600 kg	
Dimensions (WxLxH in mm)	2280 x 3610 x 2410	
Optional Ancillary Equipment	Boost pump - for longer pipe runs	
	Plate pack - for domestic hot water	
	High temperature flexible hose	
	Manifold sets for multiple boiler connection	
	Air handling units for space heating	