

Fully portable 22kW Electric Water Heater, providing domestic hot water services from a three-phase electrical supply.

- Small Footprint, Frame Mounted Package
- Dedicated Domestic Hot Water Equipment
- Tank In Tank Technology
- Dual Temperature & Pressure Gauges
- Initial Heating Time: 41 Minutes to 60°C
- Low Water Pressure Switch
- 250 Litre Storage Capacity



Detail	General	Heating	Domestic Hot Water
Output	22 kW		
Temperature Range		-	25/85°C
Fuel Type	Electric		
Power Supply	415v 3ph 50Hz		
Running Current	29.7A		
Plug Type	32A 5 Pin BS4343		
Max Working Pressure		-	Cold Water Inlet Reducing Valve 4.5 Bar
Safety Valves		-	7 Bar
BMS Outputs	No		
Time Clock	No		
Frost Protection	No		
Constant Flow	827 ltrs/hr @ 40°C		
High Limit Thermostat Protection	90°C		
Variable Temperature Control	Yes		
Storage Tank	250 ltrs		
Expansion Vessel	12 ltrs		
Flexible Hose Connections	Storz		
Water Connections	Flow / Cold Feed 1"		
Noise Level	30 dBa @ 1mtr		
Dry Weight	225 kg		
Dimensions (WxDxH)	840 x 1060 x 2050mm		
Features	Tank In Tank Technology		
	Dual Gauge Temperature/Pressure		
	Initial Heating Time: 41 Minutes to 60°C		
	Low Water Pressure Switch		